

PULLING PUNCHER 125kN

Hydraulic single acting punching tool. A mechanical pulling stud is positioned in the pre-drilled hole in order to apply the pulling force.



Punching tool 700 bar single acting :

- The manual pump with hose gives plenty of freedom to the punching head.
- Compact punching head.
- Ideal for punching electrical boxes and sign panels.
- The pump is not equipped with a hydraulic release valve. It shouldn't be used with crimping tools.

Characteristics

Operating pressure	59 MPa (590 bars)
Force	125 kN
Manual pump	590 bars simple vitesse
Hydraulic hose	1 m
Punching head	125 kN stroke 25 mm
Pulling studs	3/4in. & 3/8in. (19mm & 9,5mm)
Capacity max	Ø 100 mm - th. 3,2 mm in soft steel
Thickness max	1,6 mm stainless steel - 3,2 mm soft steel
Weight	7,6 kg
Case	Plastic carrying case

Contents of the kit

Manual pump	HP-180N 590 bars single speed hose 1m
Punching head	PDV-10 125kN
Pulling studs	3/4in. + 3/8in.
Spacers	S, M, L (Small, Medium, Large)
6 cylindrical punches	Ø 16 - 20 - 25 - 32 - 40 - 50 mm
Case	Plastic carrying case

